



**Alpha Boat**  
A division of  
Barber Welding  
Inc.  
Copyright 2005

[Click Here to  
Print Page](#) 

## Tilt Deck Trailer Models 600,620,800

	TLT-600	TLT-620	TLT-800
<b>Boat Model</b>	HB-600R	FXB-11, AM-2000 HM-2000	HS-620
<b>Dimensions</b>			
O.A.LENGTH x WIDTH	40'-0" x 8'-0" (12,19 x 2,44 m)	43'-0" x 8'-6" (13,11 x 2,59m)	46'-0" x 8'-6" (14,02 x 2,59m)
DECK LENGTH	28'-9" (8,76 m)	31'-0" (9,45 m)	35'-0" (10,67m)
NET WEIGHT	6000 lb. (2722 kg.)	7000 lb. (3130 kg.)	8000 lb. (3228 kg.)
G.V.W.(not incl. tongue weight allowance)	21000 lb. (9525 kg.)	24000 lb. (10887 kg.)	30000 lb. (13608 kg.)
<b>RUNNING GEAR:</b>			
AXLES	3 (SW) @ 7000 lb. (3175 kg.)	2 (DW) @ 12000 lb. (5443 kg.)	2 (DW) @ 15000 lb. (6804 kg.)
TIRES & SPRINGS	6 Tires @ 3500 lb. (1588 kg.)	8 Tires @ 3000 lb. (1361 kg) 4 Springs @ 6000 lb. (2722 kg.)	8 Tires @ 3750 lb. (1701 kg.) 4 Springs @ 7500 lb. (3401 kg.)
TONGUE JACK CAP	12000 lb. (5443 kg.)	12000 lb. (5443 kg.)	12000 lb. (5443 kg.)
HYDRAULIC WINCH CAPACITY	12000 lb. (5443 kg.)	12000 lb. (5443 kg.)	24000 lb. (10886 kg.)
Drive CABLE SIZE Dia. x Length Unit	1/2" x 60' (12mm x 18,2m)	1/2" x 60' (12mm x 18m)	1/2" x 80" (12mm x 24m)
<b>Options 1. Engine/Hydraulic Power Pack. (Built-in or Loose)</b>			
ENGINE OUTPUT	13 HP (9,7 kW)	13 HP (9,7 kW)	15 HP (11,2 kW)
<b>Options 2. 2. Built-in Conveyor System to use as a "Conveyor-Trailer" for Weed &amp; Trash Disposal</b>			
STORAGE CAP.	By Request		
ALL TLT SERIES HYDRAULIC TILT TRAILER FRAMES ARE CONSTRUCTED OF STRUCTURAL STEEL			
STD EQUIPMENT: PINTLE EYE HITCH * SAFETY CHAINS * SCREW JACK * ELECTRIC BRAKES BOAT TIE-DOWNS			
OPTIONAL EQUIPMENT: MOUNTED SPARE WHEEL * DRAWBAR * HYDRAULIC BRAKES			
All dimensions & weights are net, not including options: Specifications subject to change without notice			